Delfield

Specification Line®

Self-Contained Glass Door Heated Roll-In

Project _____

Item _____

Quantity _____

CSI Section 11400

Approved _____

Date _____

Specification Line®: Glass Door Heated Roll-In

Models

One section	Two section	Three section	
SSHRI1-G	SSHRI2-G	SSHRI3-G	Stainless exterior and interior glass full door
SAHRI1-G	SAHRI2-G	SAHRI3-G	Stainless exterior and aluminum interior glass full door
SMHRI1-G	SMHRI2-G	SMHRI3-G	Stainless front aluminum exterior and interior glass full door

SSHRI1-G

Standard Features

- Stainless steel interior and exterior (SS)
- Stainless steel exterior, aluminum interior (SA)
- Aluminum interior and exterior, stainless front (SM)
- Built in door locks with heavy duty strikes
- Exterior digital thermometer with high/low temperature alarm
- Easy to use electronic control
- Easy access removable shroud
- High density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane keeps energy costs low
- Stainless steel breaker strips
- Stainless steel interior door liner
- Three year parts and labor warranty

Options & Accessories

- Security (prison) package
- Door field rehingability
- Stainless steel back
- Laminate on front, sides and back
- Bottom mount electrical
- Stainless steel banking strip
- Heat shield end

Specifications

Exterior: SS and SA models shall have corrosion resistant stainless steel exterior cabinet sides, front and shroud. SM models shall have corrosion resistant aluminum on exterior cabinet sides and will have stainless front and shroud. All units shall have galvanized backs and an easily removable shroud to access components on the exterior top of the unit. All switches are accessible from the front of the unit without shroud removal.

Interior: Cabinet interior shall be corrosion resistant stainless steel (SS models) or heavy gauge aluminum (SA and SM models). Bottom and top surfaces shall be die stamped to provide radius corners and recessed floor. An incandescent light is mounted to the interior ceiling of every compartment, the switch is part of the light assembly. Door openings are protected with heavy gauge stainless steel breaker strips. Horizontal and vertical air ducts are located on the interior top and interior side of the unit. Quantity of one on one section units and two on two and three section units.

Each section can accommodate a 28.5" x 27.25" x 70.5" cart.

Doors: Double paned tempered thermopane glass. Constructed with a combination of extruded aluminum and PVC. Each door has two edgemount, self-closing, cam lift style hinges. Doors can be removed from the cabinet without the use of tools. Door handle is continuous along vertical dimension of the door. Door gaskets are magnetic and mount to the door, snapping in place and removable with out tools. Keyed door lock is mounted to the door. Lock engages into a heavy duty strike mounted to the cabinet face.

Heating system: Cabinets are designed to maintain temperatures between 120ºF and 200ºF. Heating elements are located behind the vertical ducts. The design of the heater, which is full length of the vertical duct, allows for optimal air flow and energy efficiency. Fan motor is mounted outside of the heated compartment. System is controlled by an electronic control that is accessible in the front shroud of the unit. On/Off switch is also located in the front shroud.

Electrical: Standard electrical is 208-240 Volt, 60 Hz, single phase. Unit is supplied with cord and NEMA 6-20P plug.

980 S. Isabella Rd.
Mt. Pleasant, Michigan 48858

Phone: 800-733-8948 or 989-773-7981
Fax: 800-669-0619

www.delfield.com

Manitowoc

Delfield

Specification Line®

Self-Contained Glass Door Heated Roll-In



Plan View
SSHRI1-G, SAHRI1-G, SMHRI1-G



Plan View
SSHRI2-G, SAHRI2-G, SMHRI2-G



Plan View
SSHRI3-G, SAHRI3-G, SMHRI3-G



Elevation View
SSHRI1-G, SAHRI1-G, SMHRI1-G



Elevation View
SSHRI2-G, SAHRI2-G, SMHRI2-G



Elevation View
SSHRI3-G, SAHRI3-G, SMHRI3-G



End View
All Models

Specifications

Model	V/Hz/Ph	Amps	Volume Cu.Ft.	Shelves Sq.Ft.	No. Of Shelves	Max Watts	Ship Weight	Nema Plug	Energy KW/H
SSHRI1-G, SAHRI1-G, SMHRI1-G	208-240/60/1	6.0	36.15	N/A	N/A	2160	459lbs (208kg)	6-20P	393
SSHRI2-G, SAHRI2-G, SMHRI2-G	208-240/60/1	10.5	76.34	N/A	N/A	3840	704lbs (319kg)	6-20P	648
SSHRI3-G, SAHRI3-G, SMHRI3-G	208-240/60/1	13.3	113.28	N/A	N/A	4272	1008lbs (457kg)	6-20P	N/A

Delfield reserves the right to make changes to the design or specifications without prior notice.

980 S. Isabella Rd.
Mt. Pleasant, Michigan 48858

Phone: 800-733-8948 or 989-773-7981
Fax: 800-669-0619
www.delfield.com

Printed in the U.S.A.
DSSSHRI-G
01/14

Manitowoc