Delfield

N8200G

Drop-in Self-Contained Granite Cold Slab

Project _____

Item _____

Quantity _____

CSI Section 11400

Approved _____

Date _____

Models

- N8231G 31″ granite cold slab
- N8245G 45″ granite cold slab
- N8259G 59″ granite cold slab
- N8273G 73″ granite cold slab



N8259G

Standard Features

- "Absolute Black" granite top on 14-gauge stainless steel
- Thermal mastic heat transfer compound between granite and stainless steel
- High density environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane foam
- On/Off switch located on compressor
- Stainless steel louver provided standard
- Environmentally friendly HFC-404A refrigerant
- 1.5″ deep trough around perimeter with 3/4″ stainless steel drain
- 8′ electrical cord is standard

Options & Accessories

- Relocate compressor left or right
- 220V/50C electrical
- Single or double service sneezeguards
- Remote refrigeration

Specifications

Top: Top is constructed of 14-gauge stainless steel with 3/4″ "Absolute Black" granite installed. Thermal mastic heat transfer compound is applied between the stainless steel and granite. Top is mechanically cooled with high density environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane foam throughout.

Body: 24-gauge galvanized steel. Compressor suspends below top on 16-gauge galvanized frame.

Refrigeration system: Unit uses environmentally friendly HFC-404A refrigerant. Refrigeration lines run in a serpentine pattern under stainless steel top with expansion valve as metering device. Unit is equipped with on/off switch.

Electrical connections: 115V, 60Hz single phase. Unit is wired with 3-wire, grounded, maximum. Standard with 8′ (2.4m) cord and plug.

404A REFRIGERANT

980 S. Isabella Rd.
Mt. Pleasant, Michigan 48858

Phone: 800-733-8948 or 989-773-7981
Fax: 800-669-0619

www.delfield.com

Manitowoc

N8200G: Drop-in Self-Contained Granite Cold Slab

Delfield



Drop-in Self-Contained Granite Cold Slab

N8200G

Specifications

Model	Cutout Size	H.P.	V/Hz/Ph	Amps	Nema Plug	Ship Weight
N8231G	30.75″ X 25.00″ (78cm X 64cm)	1/4	115/60/1	7.0	5-15P	258lbs/117kg
N8245G	44.63″ X 25.00″ (113cm X 64cm)	1/4	115/60/1	7.0	5-15P	330lbs/150kg
N8259G	58.50″ X 25.00″ (149cm X 64cm)	1/3	115/60/1	8.0	5-15P	401lbs/182kg
N8273G	72.38″ X 25.00″ (184cm X 64cm)	1/2	115/60/1	9.0	5-15P	473lbs/215kg

Delfield reserves the right to make changes to the design or specifications without prior notice.

980 S. Isabella Rd.
Mt. Pleasant, Michigan 48858

Phone: 800-733-8948 or 989-773-7981
Fax: 800-669-0619
www.delfield.com

Printed in the U.S.A.
DSN8200G
12/12

Manitowoc