


# KID-NU Induction

Mobile induction hot holding hob serving counter - ShelleyGlas

## KID-NU Induction

### Models

- KID1-30-NU - 1 hob hot holding counter
- KID2-36-NU - 2 hob hot holding counter
- KID3-60-NU - 3 hob hot holding counter
- KID4-74-NU - 4 hob hot holding counter



KID2-36-NU

### Standard Features

- Induction hob, control and generator provided
- One control per every (2) hobs, standard
- Up to (4) hobs connected to one generator
- One-piece, molded fiberglass pylon (base), fully rounded corners, permanent color
- All corners and center sides reinforced with bracing, laminated into the fiberglass
- Fire code rating on fiberglass
- 14 gauge galvanized bottom
- Cord and plug supplied standard
- 1 year parts and labor warranty standard

### Options & Accessories

- Counter heights available from 28" to 36"
- Tray slides and work shelves
- Food shields
- Stainless steel overshell
- Laminated exterior
- Décor packages
- Induction ready pans

### Specifications

**Top:** Exterior top is constructed of 14-gauge stainless steel, welded, ground and polished into one integral unit. Top is fabricated with square exterior corners.

**Exterior body:** Exterior body is seamless, one-piece molded fiberglass, having perfectly smooth exterior surface with all corners fully rounded. The fiberglass reinforced polyester (F.R.P) is molded with permanent color. Stress points are internally reinforced.

**Casters:** unit is mounted on 5" (13cm) diameter swivel casters with non-marking polyurethane casters and gate brakes. Overall height of caster assembly is 6" (15cm)

**Induction generator:** A generator, developed specifically for heat retaining/holding, built in an aluminum enclosure, which includes an integrated air fan and connectors in the front of the housing, that are completely protected against impacts. All connections, such as mains cable, plugs for control units, coil connection and temperature sensors are accessible from the outside. Fresh air is supplied by the fan, located at the bottom of the unit. The unit is also equipped with an air guiding system that directs the hot air out of the housing on its left and right side. With this system, a recirculation of exhausted air is not possible.

**Heat retaining plate:** The heat retaining plate is equipped with the latest RTCSmp sensor technology which enables temperature controls in real-time. The



set temperature is displayed via a 7-segment display underneath the Ceran glass. The heat retaining plate includes three (3) temperature sensors as well as the connectors for the coils and the sensors. Thanks to a space saving and compact design construction of the heat retaining plate, stand alone installations in shallow cabinets are possible.

**Control unit:** The control switch consists of a chrome sheet metal cover with a built in power switch. The power switch is enclosed in polymer housing, with high resistance to external impacts. The control switches connected with the generator via an RJ45 cable. The control unit regulates the temperature in an increment of 1°C and this from 122-212°F (50 to 100°C). The set temperature and the current temperature are shown via the 7-segment display that is located underneath the Ceran.


**Safety above all:** RTCSmp electronic temperature control that monitors the state of the induction coil, power board, CPU and the Ceran glass temperature. RTCSmp monitors the energy supply No Pan No Heat - Only if an induction suitable pan is located on the glass that energy will be consumed.






## KID-NU Induction




KID1-30-NU



KID2-36-NU



KID3-60-NU



KID4-74-NU

Specifications						
Model	# of Hob(s)	Electrical	Watts	Amps	Nema Plug	System Capacity
KID1-30-NU	1	230V, 60Hz, 1Ph	450	2	14-20P	625
KID2-36-NU	2	230V, 60Hz, 1Ph	900	3.9	14-20P	906
KID3-60-NU	3	230V, 60Hz, 1Ph	1350	5.9	14-20P	1066
KID4-74-NU	4	230V, 60Hz, 1Ph	1800	7.8	14-20P	1812

Welbilt reserves the right to make changes to the design or specifications without prior notice.