Delfield®

DSLRRI Roll-Ins

Roll-In Refrigerators w/Glass Doors

Models

☐ DSLRRI1-G ☐ DSLRRI2-G

DSLRRI2-G

Standard Features

- Stainless steel exterior and interior
- easyTouch Control with remote monitoring capability
- Stay-open door feature for easy product loading and unloading
- Door activated interior LED light
- Heavy-duty cylinder lock
- One piece, snap-in door gaskets
- Stainless steel breaker caps
- 3 silver freeze wire shelves
- 8' cord and plug
- R-290 refrigerant
- Hot gas condensate evaporator
- Adaptive defrost
- Refrigerator capable of maintaining product temperature 36°F to 38°F
- S/S finish door liner
- Accepts Carts: 26 1/2" w x 28" D x 65" H (cart not included)
  Three year parts and labor warranty and an additional 4 year compressor parts warranty.

Options & Accessories

- Stainless steel back
- Heat shield end – max temp 400 degrees
- Trim strips
- Digital control in lieu of touchscreen

Specifications

Refrigeration system: All components are mounted to the top cabinet ceiling, outside the food zone and are assembled as one piece and can be removed as one piece. Environmentally friendly R290 refrigerant is used. System has the capability of maintaining between 36˚F and 38˚F in heavy use food service operations. Utilizing a variable speed compressor, the system provides maximum efficiency and reduced energy consumption. Control system uses adaptive defrost to assure evaporator coil is free of ice and operating at optimum efficiency. Evaporator condensate is eliminated using an energy efficient hot gas system.

Units are completely insulated with high density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane.

R290

DSLRRI Roll-Ins w/Glass Doors

980 S. Isabella Rd.
Mt. Pleasant, Michigan 48858

Phone: 800-733-8948
Fax: 800-669-0619

WWW.delfield.com
8013_DEL_DSLRRI-G
09/26

WELBILT
an Ali Group Company

Delfield®

DSLRRI Roll-Ins

DSLRRI1-G



Standard Ramp Details:
28 5/8" x 3" per section with 8° slope

DSLRRI2-G



NOTE: 12" top clearance is required.
NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Delfield recommends using either an Eaton SGF20 or HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

Specifications									
Model	V/Hz/Ph	Amps	Volume Cu. Ft.	SHELF CAPACITY SQ. FT.	No. of Shelves	Unit H.P.	Btu/Hr System Cap	Ship Weight	Nema Plug
DSLRRI1-G	115/60/1	6.5	34.86	N/A	N/A	1/3	2800	490	5-15P
DSLRRI2-G	115/60/1	8.5	70.84	N/A	N/A	3/4	4950	742	5-15P

Welbilt reserves the right to make changes to the design or specifications without prior notice.

980 S. Isabella Rd.
Mt. Pleasant, Michigan 48858

Phone: 800-733-8948
Fax: 800-669-0619

WWW.delfield.com
8013_DEL_DSLRRI-G
09/26

WELBILT
an Ali Group Company